



Heavy-Duty Industrial Barcode Printer for the Most Demanding of Applications



M84PRO Series

INDUSTRY VERTICALS

- "Entry Level" Print & Apply Market
- Manufacturing
- Retail
- Supply Chain

APPLICATIONS

- Bottle & Container Labelling
- Compliance Labelling
- Food Labelling
- Circuit Board Labelling
- Serial Plate Labelling
- Surgical Equipment Labelling
- Diagnostic Kit Labelling

Heavy Duty Industrial Construction ▶

Powerful Memory ▶

Easy Connectivity ▶

Option of Increasing Print Resolution ▶

**Allows Users to Switch Print Resolution
Simply by Changing Printheads** ▶

Windows™ Compatible ▶



General Specifications

M84PRO



PRINTER MODEL		M84Pro-2	M84Pro-3	M84Pro-6
PRINTING SPECIFICATIONS				
Print Method		Direct Thermal/Thermal Transfer		
Print Resolution		8 dots/mm (203dpi)	12 dots/mm (305dpi)	24 dots/mm (609dpi)
Max. Print Speed		254mm/sec (10ips)	203mm/sec (8ips)	152mm/sec (6ips)
Max. Print Width		104mm (4.1")		
Max. Print Length		1249mm (49.21")	835mm (32.9")	356mm (14.03")
MEDIA SPECIFICATIONS				
Sensor Type		Transmissive sensor for gap, Reflective sensor for I-mark		
Media		Roll Paper: Max External Diameter 218.4mm (8.6"), Face-in Paper core Internal Diameter 76.2mm (3") Fan Fold Paper: Max Folding Height 110mm (4.33")		
Media Type (Thickness)		0.08 to 0.26mm (0.003" to 0.010")		
Media Size	Continuous	Width: 22 to 125mm (0.87" to 4.93"), inclusive backing paper size 25 to 128 mm (0.99" to 5.04") Pitch: 6 to 356mm (0.24" to 14.03"), inclusive backing paper size 9 to 359 mm (0.35" to 14.14")		
	Tear OFF	Width: 22 to 125mm (0.87" to 4.93"), inclusive backing paper size 25 to 128 mm (0.99" to 5.04") Pitch: 16 to 356mm (0.63" to 14.03"), inclusive backing paper size 19 to 359 mm (0.75" to 14.14")		
	Cutter / Dispensing	Width: 22 to 125mm (0.87" to 4.93"), inclusive backing paper size 25 to 128 mm (0.99" to 5.04") Pitch: 30 to 356mm (1.18" to 14.03"), inclusive backing paper size 33 to 359 mm (1.30" to 14.14")		
MEMORY PROCESSING				
Memory		Flash memory 2MB. Expandable memory 4MB		
CPU		32 bit RISC		
COMMUNICATION INTERFACES				
Plug in Interface Cards		Serial - RS232C Parallel - IEEE1284 Ethernet - 10/100BaseT Wireless 802.11g RS422/485		
Others		USB External Connector Port		
FONTS/BARCODE SYMBOLOGIES				
Internal Fonts		XU 5x9 dots, XS 17x17 dots, XM 24x24 dots, XB 48x48 dots, XL 48x48 dots OCR-A 15x22 dots OCR-A 22x33 dots OCR-A 44x66 dots OCR-B 20x24 dots OCR-B 30x36 dots OCR-B 60x72 dots		
Internal Raster Fonts		CG Times, CG Triumvirate		
Barcodes	1D Barcode	UPC-A/E, EAN, JAN, CODE 39, CODE 93, CODE 128, UCC/EAN 128, Inter-leaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, NW-7, MSI, Postnet, Bookland		
	2D Barcode	QRCode, PDF 417, MaxiCode, Data Matrix		
	Character Rotation	0°, 90°, 180°, 270° rotation		
OPERATING & ENVIRONMENTAL				
Power Consumption		AC 100 / 230V +/- 10% Peak 190VA 130W (Standby 24VA 16W)		
Environment		Operating Environment: 5 to 40°C / 30 to 80% (with no condensation) Storage Environment: -5 to 60°C / 30 to 90% (with no condensation)		
Dimensions		(W x D x H): 265 x 435 x 335 mm (10.44" x 17.14" x 13.12")		
Weight		18.5kg (standard)		
Regulatory		VCCI (Class B), FCC (Class B), UL, CUL, CE		
ACCESSORIES & OPTIONS				
Options		Cutter unit, Dispensing unit, Rewinder		

Contact For more information about SATO around the globe, visit www.satoworldwide.com

AMERICAS

10350A Nations Ford Road Charlotte, NC
28273
Tel: (704) 644-1650
Fax: (704) 644-1662
E: satosales@satoamerica.com

ASIA PACIFIC & OCEANIA

438B, Alexandra Road,
#09-01/02, Alexandra Technopark
Singapore 119968
Tel: (65) 6271-5300
Fax: (65) 6273-6011
E: sales@satoasiapacific.com

EUROPE

Lambroekstraat 5A, 1831 Diegem, Belgium
Tel: (32) 2 719 03 90
Fax: (32) 2 719 03 99
E: info@be.satoeurope.com

For sales & general enquiries: sales@satogbs.com