

M-11

2D Imager scanner

The M-11 is an omni-directional scanner for on top of the counter as built-in. Offering our high performance 2D CMOS Imager along with a well thought out design.



The M-11; excellent versatile presentation scanner

This presentation scanner can be used on top of the counter, but it can be easily built-in as well. This typically omni-directional scanner enables faster checkout throughput and executes mobile marketing programs more easily. This compact and modern design with an excellent performance makes it suitable for applications ranging from point-of-sale to healthcare.



Highlights

- Supports all common 1D & 2D codes
- Omni directional scanning
- Imaging for mobile coupons
- 360° high speed reading
- High speed scanning; 120 fps
- Several trigger options
- Flexible cable outlet - 4 directions

M-11

Product Specifications

Operating indicators

Visual: 2 LEDs (red, green, blue)

Non-visual: built-in speaker, tone adjustable

Communication

USB: Full-speed 12Mbps (HID/COM)

Power

Voltage requirement: 4.5 - 5.5V (USB)

2D Imager Optics

Light source: 2 LEDs light source - 2 warm white aiming LEDs

Scan method: monochrome CMOS area sensor, 1280 x 800 pixels

Scan rate: up to 120 fps

Image format: Windows Bitmap, JPEG

Reading pitch angle: ±60°

Reading skew angle: ±70°

Reading tilt angle: 360°

Min. PCS value: 0.3

Min. resolution at PCS 0.9: 0.1 mm (Code 39)

Depth of field at code 39:

35 - 88 mm / 1.38 - 3.46 in (0.127 / 5 mil)

Depth of field at UPC/EAN: 0 - 198 mm / 0 - 7.8 in

(0.26 / 10.2 mil), 0 - 234 mm / 0 - 9.2 in (0.33 / 13 mil)

Depth of field at QR code:

0 - 142 mm / 0 - 5.59 in (0.381 / 15 mil)

Depth of field at Datamatrix:

28 - 99 mm / 1.1 - 3.9 in (0.254 / 10 mil)

Motion tolerance: UPC 0.33 mm, 2.54 m/s

Supported symbologies

Barcode (1D): JAN/UPC/EAN incl. add on, Codabar / NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/Plessey, UK/Plessey, S-Code, Telepen, Tri-Optic, USPS

Postal code: Chinese Post, Intelligent Mail Barcode, Korean Postal Authority code, Dutch KIX code, UK Postal, Postal JPN, POSTNET, PLANET

2D code: Aztec Code, Aztec Runes, Composite codes, Codablock F, Data Matrix (ECC200), Maxi Code, MicroPDF417, Micro QR Code, Passport MRZ (OCR-B), PDF417, QR Code

Durability

Temperature in operation: -5 to 45 °C / 23 to 113 °F

Temperature in storage: -30 to 60 °C / -22 to 140 °F

Humidity in operation: 10% to 90% (non-condensing)

Humidity in storage: 10% to 90% (non-condensing)

Ambient light immunity: Fluorescent 10,000 lx max, direct sun 100,000 lx max

Drop test: 1.5 m / 5 ft drop onto concrete surface

Vibration test: 10 - 100 Hz with 2G for 30 min.

Protection rate: IP42

Physical

Dimensions (W x H x D): 84.4 x 48 x 124.4 mm / 3.32 x 1.89 x 4.9 in.

Cable length: 2.1 m

Weight body: Ca. 220 g / 7.44 oz

Regulatory & safety

Product compliance: CE, FCC, VCCI, IEC62471:2006, EN55032, EN55024, RoHS

Models

Interface options: USB

Color versions: Black

Authorized Australian Distributor: Goodson Imports Pty Ltd, Representation in all main States and New Zealand,
Head Office: 9 Liberty Road, Huntingwood NSW 2148, Sydney Australia
Ph: 02-8875 4544 Fax 02-8875 4588, www.goodson.com.au